

TKE/P 32+



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

| | |
|---------------------------------|---------------|
| Material cable gland | Polyamide |
| Material sealing gasket | EPDM |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP66 |
| Product Color | RAL 7035 |
| Thread type | M |
| Ø Connection thread D | 32 |
| Lead | 1,5 |
| Length screw-in thread L | 12 mm |
| Key width SW | 36 mm |
| Total length TL | 42 mm - 51 mm |
| Glow wire test | 750 °C |
| Type of cable anchorage | A |
| Install. torques fitting | 15 N/m |
| Install. torques cap nut | 4 N/m |
| Impact category | 4 |
| Order no. RAL 7035 | 10111319 |
| Type | TKE/P 32+ |
| Packing unit | 1 |
| ETIM-Classification | EC000441 |

Description:

IP 68 Plastic cable gland. ESKV 32+/ MFD 2 x 25mm Tails and 1 x 16mm Earth. Kit contains insert, locknut and blanking insert.

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

24.03.2022

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk