

**0.5W** 0.5W at 24V DC

 Frosted effect for low glare and soft lighting

 Low voltage ground light

## WARRANTY

Warranty 7 years

## FEATURES & BENEFITS

Robust cable for outdoor use

Shallow depth for easy installation

Coastal protected

Easy and quick installation with parallel wiring



## GL018 C

0.4W, 4lm mini round marker ground light

### FEATURES

<b>IP rating</b>	IP68
<b>IK rating</b>	IK07
<b>CSP Switchable</b>	Single CCT
<b>Tiltable (°)</b>	Fixed
<b>LED Lifetime</b>	L70 30,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3
<b>Walk Over / Drive Over</b>	Walk over

### INSTALLATION INFORMATION

<b>Input</b>	24V DC
<b>Maximum Ambient Temperature</b>	35°C
<b>Weight</b>	0.1355Kg
<b>Inrush Current</b>	N/A
<b>Cut Out Size</b>	28
<b>Construction Material</b>	Stainless steel (316)
<b>UK Bathroom Zone</b>	0
<b>SELV</b>	N/A
<b>Electric Class (1, 2, 3)</b>	III
<b>Earth Leakage</b>	N/A
<b>Suitable for coastal areas</b>	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m
<b>GL018 C NW</b>	Stainless steel	0.4W	4000K	120°	4	10	1
<b>GL018 C 27</b>	Stainless steel	0.4W	2700K	120°	4	10	1
<b>GL018 C WARM WHITE</b>	Stainless steel	0.4W	3000K	120°	4	10	1
<b>GL018 C BLUE</b>	Stainless steel	0.4W	Blue	120°	0.5	1.3	0.18

Energy rating is a reflection of the LED light source.

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Parallel
<b>Input Cable Type</b>	H05RN-F (6MM OD) 2 CORE

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PS1524	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	30
PS3024B	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	60
LSD6024	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	120

### ACCESSORIES

<b>JB1 / JB5 / JB6</b>	IP68 waterproof connectors	Sold Separately
<b>PDCINT1-10V</b>	1-10V dimming interface for use with 24V LED drivers	Sold Separately

BEAM ANGLE: **120°**

