



1W at 350mA or 2W at 700mA



Coastal protected



Low voltage step light

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Asymmetric beam angle

0% upward light spill

Recess into a wall, floor or ceiling

Suitable for indoor and outdoor use

33mm cut-out size

PATENT: [GB2544975 EP3176502](#)



GL019 EYELID

Asymmetric beam angle with zero upward light spill

FEATURES

IP rating	IP68
IK rating	Other
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	No

INSTALLATION INFORMATION

Input	350mA / 700mA DC
Maximum Ambient Temperature	50°C
Weight	120g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Anodised aluminium
UK Bathroom Zone	0
SELV	N/A
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
GL019E30SS	Stainless steel	50°	1W (350mA)	3000K	41	41	3.5	
			2W (700mA)	3000K	72	36	3.5	
GL019E27SS	Stainless steel	50°	1W (350mA)	2700K	36	36	3.1	
			2W (700mA)	2700K	63	31	3.1	
GL019E30BL	Black	50°	1W (350mA)	3000K	36	36	2.1	
			2W (700mA)	3000K	64	32	2.1	
GL019E27BL	Black	50°	1W (350mA)	2700K	31	31	1.8	
			2W (700mA)	2700K	56	28	1.8	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700 (all settings)	220-240V	Yes	No	N/A		
DRV350700TD (700mA)	220-240V	Yes	Yes	N/A		
PSIP70018W	220-240V	Yes	No	0	1	8

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately

BEAM ANGLE: 50°

