

5.7W

Coastal protected

IP65 ideal for outdoor environments

## FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution.

Straight to mains wall light, perfect for framing entrances and illuminating columns

Anodised Aluminium is sleek and durable

Long lifetime of 70,000hrs

## WL075

Straight to mains, high output LED wall light

### FEATURES

|                        |             |
|------------------------|-------------|
| IP rating              | IP65        |
| CSP Switchable         | Single CCT  |
| Dimmable Option        | No          |
| LED Lifetime           | L70 70,000h |
| Colour Rendering Index | CRI>80      |
| Colour Consistency     | SDCM3       |

### INSTALLATION INFORMATION

|                             |                    |
|-----------------------------|--------------------|
| Input                       | 220-240V AC        |
| Maximum Ambient Temperature | 40°C               |
| Weight                      | 1.2kg              |
| Inrush Current              | 60A 0.037ms        |
| Construction Material       | Anodised aluminium |
| UK Bathroom Zone            | 2                  |
| Electric Class (1, 2, 3)    | I                  |
| Suitable for coastal areas  | Yes                |

### PHOTOMETRICS @ 25°C

| Product code | Finish | W    | Colour | Beam | lm  | lm/W | Lx @ 1m | Energy                                                                                |
|--------------|--------|------|--------|------|-----|------|---------|---------------------------------------------------------------------------------------|
| WL075SNBM27  | Silver | 5.7W | 2700K  | 110° | 515 | 90   | 2763    |  |
| WL075SNBM30  | Silver | 5.7W | 3000K  | 110° | 520 | 91   | 2789    |  |
| WL075SNBM40  | Silver | 5.7W | 4000K  | 110° | 530 | 93   | 2843    |  |
| WL075BNBM27  | Black  | 5.7W | 2700K  | 110° | 515 | 90   | 2763    |  |
| WL075BNBM30  | Black  | 5.7W | 3000K  | 110° | 520 | 91   | 2789    |  |
| WL075BNBM40  | Black  | 5.7W | 4000K  | 110° | 530 | 93   | 2843    |  |
| WL075ZNBM27  | Bronze | 5.7W | 2700K  | 110° | 515 | 90   | 2763    |  |
| WL075ZNBM30  | Bronze | 5.7W | 3000K  | 110° | 520 | 91   | 2789    |  |

### WIRING INFORMATION

|                         |          |
|-------------------------|----------|
| Cable / Flying Lead     | 0.3m     |
| Type of Wiring Required | Parallel |

### LED DRIVER

| Driver                       | Input    | SELV | Dimming | Bathroom Zone | Min | Max |
|------------------------------|----------|------|---------|---------------|-----|-----|
| N/A (integrated SELV driver) | 220-240V | Yes  | No      | N/A           | N/A | N/A |

### ACCESSORIES

|                         |
|-------------------------|
| No accessories required |
|-------------------------|