

5.1W

Coastal protected

IP65 ideal for outdoor environments

FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution.

Ideal for framing entrances and illuminating columns with its bi-directional lights

Anodised Aluminium is sleek and durable

Long lifetime of 70,000hrs

Mains voltage wall light

WL070

Straight to mains, high output LED wall light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	0.9kg
Inrush Current	60A 0.037ms
Construction Material	Anodised aluminium
UK Bathroom Zone	2
Electric Class (1, 2, 3)	I
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL070SNBM27	Silver	5.1W	2700K	12°	510-255	100	3147-1573	
WL070SNBM30	Silver	5.1W	3000K	12°	550-275	108	3394-1697	
WL070SNBM40	Silver	5.1W	4000K	12°	560-280	110	3455-1727	
WL070BNBM27	Black	5.1W	2700K	12°	510-255	100	3147-1573	
WL070BNBM30	Black	5.1W	3000K	12°	550-275	108	3394-1697	
WL070BNBM40	Black	5.1W	4000K	12°	560-280	110	3455-1727	
WL070CNBM27	Copper	5.1W	2700K	12°	510-255	100	3147-1573	
WL070ZNB27	Bronze	5.1W	2700K	12°	510-255	100	3147-1573	
WL070ZNB30	Bronze	5.1W	3000K	12°	550-275	108	3394-1697	
WL070CNBM30	Copper	5.1W	3000K	12°	550-275	108	3394-1697	

WIRING INFORMATION

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	N/A	N/A	N/A

ACCESSORIES

No accessories required
