

Luminaires | Ground

## RGBCX Spike Light

80105



### Photometrics

<b>Wattage</b>	6
<b>Lumens</b>	575
<b>Lm/W</b>	92
<b>Beam Angle</b>	25
<b>Colour Temperature</b>	RGB + 2700 / 3000 / 4000 / 6500

### Product Features

<b>Brand</b>	Aurora
<b>IP Rating</b>	IP66
<b>IK Rating</b>	IK08
<b>L70 Hours</b>	50,000
<b>Lifetime Class</b>	L70
<b>SKU Type</b>	Dim
<b>Dimmable</b>	YES
<b>Warranty</b>	3 Years
<b>Country of Origin</b>	CN

### Electrical Specification

<b>Input Voltage (Min)</b>	100
----------------------------	-----

<b>Input Voltage (Max)</b>	240
<b>Input Voltage Type</b>	AC
<b>Protection Class</b>	Class 1
<b>Frequency (Min) Hz.</b>	50
<b>Frequency (Max) Hz.</b>	60
<b>Operating Temp. (Min) °C</b>	-20
<b>Operating Temp. (Max) °C</b>	45

## Physical Attributes

<b>Width (mm)</b>	60
<b>Height (mm)</b>	110
<b>Overall Diameter (mm)</b>	60
<b>Material</b>	Aluminium
<b>Optic Material</b>	Glass
<b>Finish Colour</b>	Black

## Features

<b>Marketing Feature 1</b>	RGBCX (White can be controlled between 2700K and 6500K)
<b>Marketing Feature 2</b>	Robust Aluminium and Glass housing
<b>Marketing Feature 3</b>	Pre-wired with 850mm of cable for flexible installation
<b>Marketing Feature 4</b>	Mounting stake included in the box