



## GL021

30° slotted LED ground / step light

### FEATURES

<b>IP rating</b>	IP68
<b>IK rating</b>	IK07
<b>CSP Switchable</b>	Single CCT
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3
<b>Walk Over / Drive Over</b>	Walk over

### INSTALLATION INFORMATION

<b>Input</b>	350mA DC
<b>Maximum Ambient Temperature</b>	35°C
<b>Weight</b>	296g
<b>Inrush Current</b>	N/A
<b>Cut Out Size</b>	50
<b>Construction Material</b>	Stainless steel (316)
<b>UK Bathroom Zone</b>	0
<b>SELV</b>	N/A
<b>Electric Class (1, 2, 3)</b>	III
<b>Earth Leakage</b>	N/A
<b>Suitable for coastal areas</b>	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
<b>GL021 NW</b>	Stainless steel	1W	4000K	30°	10	10	10	
<b>GL021 WARM WHITE</b>	Stainless steel	1W	3000K	30°	8	8	8	

Energy rating is a reflection of the LED light source.

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Series
<b>Input Cable Type</b>	H05RN-F (6MM OD) 2 CORE

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV350700TD (350 & 500mA)	220-240V	Yes	Yes	N/A		
PSIP3509W	220-240V	Yes	No	0	1	8
PSIP35018W	220-240V	Yes	No	1		

### ACCESSORIES

<b>JB2 / JB4 / JB6</b>	IP68 waterproof connectors	Sold Separately
<b>TUBE/50</b>	Installation tube	Sold Separately
<b>WCR 275 BLACK</b>	2-core rubber cable	Sold Separately

**1W** 1W at 350mA



Coastal protected



Low voltage groundlight

### WARRANTY

Warranty

7 years

### FEATURES & BENEFITS

Angled light, ideal for use as a step light

Robust cable for outdoor use

Brushed stainless steel for sleek effect

BEAM ANGLE: **30°**

