

ACCESSORY SELECTION

Use the table below to match Trident Power Plus 6 cable sizes with the supplier-listed gland size and Telecleat selection. The values have been reformatted from the UK Cables sheet for clearer use on product pages and by installers.

Cable size	Nominal O/D (mm)	Gland	Cleat No.	Max O/D (mm)	Telecleat Ref	Telecleat range (mm)
UNARMoured						
3 x 4.0	14.9	20(S)	6	15.2	385AA02	12.2-16.7
3 x 6.0	16	20	7	17.8	385AA03	14.6-19.8
3 x 10.0	16.7	20	7	17.8	385AA03	14.6-19.8
3 x 16.0	18.8	20	8	20.3	385AA03	16.6-19.8
5 x 6.0	18.7	20	8	20.3	385AA03	16.6-19.8
5 x 10.0	19.7	25	9	22.8	385AA04	17.7-24.0
5 x 16.0	22.4	25	10	25.4	385AA04	17.7-24.0
ARMoured						
3 x 4.0	18.2	20	8	20.3	385AA04	17.7-24.0
3 x 6.0	20	20	9	22.8	385AA04	17.7-24.0
3 x 10.0	20.7	25	9	22.8	385AA04	17.7-24.0
3 x 16.0	22.5	25	10	25.4	385AA04	17.7-24.0
5 x 6.0	22.7	25	10	25.4	385AA04	17.7-24.0
5 x 10.0	23.7	25	10	25.4	385AA05	21.7-28.5
5 x 16.0	26.9	32	11	27	385AA05	21.7-28.5

Important: Nominal/max outside diameters, gland sizes, cleat numbers and Telecleat references are reproduced from the UK Cables supplier sheet. Confirm the actual cable O/D and the accessory suitability for the installation before fitting.

Source: UK Cables - Trident Power Plus 6 accessory selection sheet supplied to Electrical4Less.