



WL070

Black straight to mains, high output LED wall light

Features

IP rating	IP65
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	0.9kg
Inrush Current	60A 0.037ms
Construction Material	Anodised aluminium
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL070SNBM27	Silver	5.1W	2700K	12°	510 / 255	100	3147 / 1573	
WL070SNBM30	Silver	5.1W	3000K	12°	550 / 275	108	3394 / 1697	
WL070SNBM40	Silver	5.1W	4000K	12°	560 / 280	110	3455 / 1727	
WL070BNBM27	Black	5.1W	2700K	12°	510 / 255	100	3147 / 1573	
WL070BNBM30	Black	5.1W	3000K	12°	550 / 275	108	3394 / 1697	
WL070BNBM40	Black	5.1W	4000K	12°	560 / 280	110	3455 / 1727	
WL070CNBM27	Copper	5.1W	2700K	12°	510 / 255	100	3147 / 1573	
WL070ZNBM27	Bronze	5.1W	2700K	12°	510 / 255	100	3147 / 1573	
WL070ZNBM30	Bronze	5.1W	3000K	12°	550 / 275	108	3394 / 1697	
WL070CNBM30	Copper	5.1W	3000K	12°	550 / 275	108	3394/1697	

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

Accessories

N/A	No accessories required
-----	-------------------------



5.1W



Coastal protected



IP65 ideal for outdoor environments

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution.
- Ideal for framing entrances and illuminating columns with its bi-directional lights
- Anodised Aluminium is sleek and durable
- Long lifetime of 70,000hrs
- Mains voltage wall light

Beam angle: 12°

