



5.1W



Coastal protected



IP65 ideal for outdoor environments

WL070

Copper straight to mains, high output LED wall light

Features

IP rating	IP65
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRi>80
Colour Consistency	SDCM3

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	0.9kg
Inrush Current	60A 0.037ms
Construction Material	Copper
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution.
- Ideal for framing entrances and illuminating columns with its bi-directional lights
- Anodised Aluminium is sleek and durable
- Long lifetime of 70,000hrs
- Mains voltage wall light

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL070SNBM27	Silver	5.1W	2700K	12°	510 / 255	100	3147 / 1573	AIG E
WL070SNBM30	Silver	5.1W	3000K	12°	550 / 275	108	3394 / 1697	AIG E
WL070SNBM40	Silver	5.1W	4000K	12°	560 / 280	110	3455 / 1727	AIG E
WL070BNBM27	Black	5.1W	2700K	12°	510 / 255	100	3147 / 1573	AIG E
WL070BNBM30	Black	5.1W	3000K	12°	550 / 275	108	3394 / 1697	AIG E
WL070BNBM40	Black	5.1W	4000K	12°	560 / 280	110	3455 / 1727	AIG E
WL070CNBM27	Copper	5.1W	2700K	12°	510 / 255	100	3147 / 1573	AIG E
WL070ZNBM27	Bronze	5.1W	2700K	12°	510 / 255	100	3147 / 1573	AIG E
WL070ZNBM30	Bronze	5.1W	3000K	12°	550 / 275	108	3394 / 1697	AIG E
WL070CNBM30	Copper	5.1W	3000K	12°	550 / 275	108	3394/1697	AIG E

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

Accessories

N/A	No accessories required
-----	-------------------------

Beam angle: 12°

