



5.1W



Coastal protected



IP65 ideal for outdoor environments

WL070

Bronze straight to mains, high output LED wall light

Features

| | |
|------------------------|-------------|
| IP rating | IP65 |
| CSP Switchable | Single CCT |
| Dimmable Option | No |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRi>80 |
| Colour Consistency | SDCM3 |

Installation Information

| | |
|-----------------------------|--------------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 40°C |
| Weight | 0.9kg |
| Inrush Current | 60A 0.037ms |
| Construction Material | Anodised aluminium |
| UK Bathroom Zone | 2 |
| SELV | Yes |
| Electric Class (1, 2, 3) | 1 |
| Earth Leakage | 0.1mA |
| Suitable for coastal areas | Yes |

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution.
- Ideal for framing entrances and illuminating columns with its bi-directional lights
- Anodised Aluminium is sleek and durable
- Long lifetime of 70,000hrs
- Mains voltage wall light

Photometrics @ 25°C

| Product Code | Finish | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|--------|------|--------|------|-----------|------|-------------|--------|
| WL070SNBM27 | Silver | 5.1W | 2700K | 12° | 510 / 255 | 100 | 3147 / 1573 | AIG E |
| WL070SNBM30 | Silver | 5.1W | 3000K | 12° | 550 / 275 | 108 | 3394 / 1697 | AIG E |
| WL070SNBM40 | Silver | 5.1W | 4000K | 12° | 560 / 280 | 110 | 3455 / 1727 | AIG E |
| WL070BNBM27 | Black | 5.1W | 2700K | 12° | 510 / 255 | 100 | 3147 / 1573 | AIG E |
| WL070BNBM30 | Black | 5.1W | 3000K | 12° | 550 / 275 | 108 | 3394 / 1697 | AIG E |
| WL070BNBM40 | Black | 5.1W | 4000K | 12° | 560 / 280 | 110 | 3455 / 1727 | AIG E |
| WL070CNBM27 | Copper | 5.1W | 2700K | 12° | 510 / 255 | 100 | 3147 / 1573 | AIG E |
| WL070ZNBM27 | Bronze | 5.1W | 2700K | 12° | 510 / 255 | 100 | 3147 / 1573 | AIG E |
| WL070ZNBM30 | Bronze | 5.1W | 3000K | 12° | 550 / 275 | 108 | 3394 / 1697 | AIG E |
| WL070CNBM30 | Copper | 5.1W | 3000K | 12° | 550 / 275 | 108 | 3394/1697 | AIG E |

Energy rating is a reflection of the LED light source.

Wiring Information

| | |
|-------------------------|----------|
| Cable / Flying Lead | 0.3m |
| Type of Wiring Required | Parallel |

LED Driver

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|------------------------------|----------|------|---------|---------------|-----|-----|
| N/A (integrated SELV driver) | 220-240V | Yes | No | 2 | N/A | N/A |

Accessories

| | |
|-----|-------------------------|
| N/A | No accessories required |
|-----|-------------------------|

Beam angle: 12°

