



5.7W



Coastal protected



IP65 ideal for outdoor environments

WL075

Bronze straight to mains, high output LED wall light

Features

IP rating	IP65
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	1.2kg
Inrush Current	60A 0.037ms
Construction Material	Anodised aluminium
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution.
- Straight to mains wall light, perfect for framing entrances and illuminating columns
- Anodised Aluminium is sleek and durable
- Long lifetime of 70,000hrs

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL075SNBM27	Silver	5.7W	2700K	110°	515	90	2763	AIG E
WL075SNBM30	Silver	5.7W	3000K	110°	520	91	2789	AIG E
WL075SNBM40	Silver	5.7W	4000K	110°	530	93	2843	AIG E
WL075BNBM27	Black	5.7W	2700K	110°	515	90	2763	AIG E
WL075BNBM30	Black	5.7W	3000K	110°	520	91	2789	AIG E
WL075BNBM40	Black	5.7W	4000K	110°	530	93	2843	AIG E
WL075ZNBM27	Bronze	5.7W	2700K	110°	515	90	2763	AIG E
WL075ZNBM30	Bronze	5.7W	3000K	110°	520	91	2789	AIG E

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

Accessories

N/A	No accessories required
-----	-------------------------

Beam angle: 110°

