



WL340

Asymmetric, straight to mains, step light

Features

IP rating	IP65
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	1100g
Inrush Current	9A 0.8ms
Cut Out Size	80
Construction Material	Antique Brass
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL340NW	Stainless steel		2.6W	4000K	50°	59	22	65	A B F
WL340WW	Stainless steel		2.6W	3000K	50°	50	19	54	A B F
WL340AB27	Antique brass	Antique Brass	2.6W	2700K	50°	49	19	52	A B G
WL340ABWW	Antique brass	Antique Brass	2.6W	3000K	50°	50	19	54	A B F

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

Accessories

Installation Tube	For easy ground installation	Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately



collingwood



2.6W



Coastal protected



Main voltage step light

Guarantee

Warranty 7 years

Features & benefits

- Installation tube included
- Ideal for illuminating walls, steps and pathways

Beam angle: 50°

