



11.4W



Coastal protected



IP65 ideal for outdoor areas

SL230 Mains

Mains voltage LED twin pole spike light

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	90°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRi>80
Colour Consistency	SDCM3
Rotation Angle	330°

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	SL230B: 1578g SL230D: 3500g SL230Z: 1577g
Inrush Current	120A 37ms
Construction Material	Anodised aluminium
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Adjustable pole-mounted twin heads are perfect for illuminating paths, steps and trees
- Easily ground mounted with spiked pole and single cable for quick installation
- Elegant and discreet black and bronze finishes
- Mains voltage for easy installation
- Highly efficiency of 93lm/W

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
SL230ZWBM30	Bronze anodised aluminium	11.4W	3000K	40°	1040	2 x 91	2 x 1182	
SL230BWBM27	Black anodised aluminium	11.4W	2700K	40°	1030	2 x 90	2 x 1171	
SL230BWBM30	Black anodised aluminium	11.4W	3000K	40°	1040	2 x 91	2 x 1182	
SL230DWBM27	Stainless steel	11.4W	2700K	40°	1030	2 x 90	2 x 1171	
SL230DWBM30	Stainless steel	11.4W	3000K	40°	1040	2 x 91	2 x 1182	

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	(H05RN-F) 3 CORE rubberised cable (OD: 7mm)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	N/A

Accessories

JB5	Gel filled waterproof connector	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately

Beam angle: 40°

