



WL95

IP65 CCT & wattage switchable bulkhead with white housing & conduit entries

Features

IP rating	IP65
IK rating	IK10
CSP Switchable	Switchable CCT
Sensor Option	Microwave (Step-Dim)
Dimmable Option	No
LED Lifetime	L70 35,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	1,030g
Inrush Current	10A 50ms
Construction Material	ABS housing PC diffuser
UK Bathroom Zone	2
Electric Class (1, 2, 3)	2
Install Connector Type	4 ways, push-fit
Mounting Options	Ceiling & wall
Power Factor	0.9

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	lx@1m	EM lm	Energy
WL9527SCS	White	Standard	115°	18W	3000K	2100	116	695	-	
					4000K	2150	119	712	-	
					6500K	2150	119	712	-	
				27W	3000K	3100	114	695	-	
					4000K	3200	118	712	-	
					6500K	3200	118	712	-	
WL9527ECS	White	Emergency	115°	18W	3000K	2100	116	695	120	
					4000K	2150	119	712	120	
					6500K	2150	119	712	120	
				27W	3000K	3100	114	695	120	
					4000K	3200	118	712	120	
					6500K	3200	118	712	120	
WL9527MCS	White	Microwave sensor	115°	15W	3000K	1650	110	546	-	
					4000K	1750	116	579	-	
					6500K	1750	116	579	-	
				25W	3000K	2800	112	546	-	
					4000K	3000	120	579	-	
					6500K	3000	120	579	-	
WL9527CCS	White	Emergency Microwave sensor	115°	15W	3000K	1650	110	546	120	
					4000K	1750	116	579	120	
					6500K	1750	116	579	120	
				25W	3000K	2800	112	546	120	
					4000K	3000	120	579	120	
					6500K	3000	120	579	120	
WL9527SCSB	Black	Standard	115°	18W	3000K	2100	116	695	-	
					4000K	2150	119	712	-	
					6500K	2150	119	712	-	
				27W	3000K	3100	114	695	-	
					4000K	3200	118	712	-	
					6500K	3200	118	712	-	
WL9527ECBS	Black	Emergency	115°	18W	3000K	2100	116	695	120	
					4000K	2150	119	712	120	
					6500K	2150	119	712	120	
				27W	3000K	3100	114	695	120	
					4000K	3200	118	712	120	
					6500K	3200	118	712	120	
WL9527MCSB	Black	Microwave sensor	115°	15W	3000K	1650	110	546	-	
					4000K	1750	116	579	-	
					6500K	1750	116	579	-	



collingwood



CCT switchable between 3000K, 4000K & 6500K



Wattage switchable between 18W & 27W



Emergency option available



Guarantee

Warranty 3 years

Features & benefits

- Slimline design
- Multiple mounting options: BESA box, M20 conduit, cable glands
- IP65 rated, making it perfect for using outdoors
- High efficacy of 120lm/W
- Multiple black bezel options available
- Easy access push fit screwless terminals
- Microwave step-dim dusk-down sensor, which is programmable by dip switches, saving energy by having it on only when needed
- Flicker free, resulting in a more comfortable setting

Beam angle: 115°



Bulkheads specification sheet

WL9527CCSB	Black	Emergency Microwave sensor	115°	25W	3000K	2800	112	546	-	
					4000K	3000	120	579	-	
					6500K	3000	120	579	-	
				15W	3000K	1650	110	546	120	
					4000K	1750	116	579	120	
					6500K	1750	116	579	120	
				25W	3000K	2800	112	546	120	
					4000K	3000	120	579	120	
					6500K	3000	120	579	120	

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	Push-fit terminals, 1.5mm² max, loop-in/loop-out.
Type of Wiring Required	Parallel

Accessories

WL95BEW	White Eyelid Accessory	Sold Separately
---------	------------------------	-----------------



Bulkheads are a simple yet functional product that offer a practical solution for lighting commercial spaces, corridors and stairways, as well as indoor and outdoor communal spaces. With a high efficacy and a choice of two lumen levels, this easy install, colour switchable light is a robust and durable option.