



Mounting brackets slide full length of luminaire

Tool-less Installation

PIR Sensor accessory



Colour switchable between 3000K 4000K & 6500K



IP66 for total dust ingress protection



IK10 rated high resistance against impact and vandalism

Polas Versa

Colour switchable Batten with IP66 protection perfect for all applications

Features

IP rating	IP66
IK rating	IK10
CSP Switchable	Switchable CCT
UGR	UGR<22
Sensor Option	Microwave & PIR options
Dimmable Option	No
LED Lifetime	L80 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	No

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	1kg
Inrush Current	13.6A 328us
Construction Material	Anti-UV Polycarbonate
SELV	No
Electric Class (1, 2, 3)	1
Install Connector Type	Push-fit terminal, loop-in/loop-out
UK Building Regulations	Part P
Mounting Options	Ceiling
Power Factor	0.9

Guarantee

Warranty 5 years

Features & benefits

- Tool-less installation method making for a fast installation
- Designed for industrial and residential applications
- Lightweight for easy handling
- Through-wired as standard so luminaires when wired together light up as a group
- Mounting brackets slide entire length of luminaire to help make refurbishment easier

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy
POL30104	White	Standard	120°	43W	3000K	6300	149	
					4000K	6600	153	
					6500K	6500	153	
POL30304	White	DALI Dimmable	120°	43W	3000K	6400	149	
					4000K	6600	153	
					6500K	6500	153	

Energy rating is a reflection of the LED light source.


Wiring Information

Type of Wiring Required	Parallel
-------------------------	----------


Accessories

POL30504	Polas Versa PIR Sensor	Sold Separately
----------	------------------------	-----------------

Beam angle: 120°



1600mm



65mm

