Datasheet
SKU: AU-ST800IP/30

Luminaires | Strip

ChromaFlex IP67 Opal COB LED Strip

AU-ST800IP/30

Photometrics

Wattage	9.6
Lumens	1050
Lm/W	110
Beam Angle	120
Colour Temperature	3000
Ra	90
SDCM	6

Product Features

Brand	Aurora
IP Rating	IP67
L80 Hours	50,000
Lifetime Class	L80 B10
Dimmable	RF / Triac / Casambi / Dali / 1-10V / KNX
Warranty	5 Years
Country of Origin	CN

Electrical Specification

Input Voltage (Min)	24

Input Voltage Type	DC
Power Factor	1
Protection Class	Class 3
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40

Physical Attributes

Length (mm)	50000mm
Width (mm)	10mm
Height (mm)	4.5mm
Material	PCB+LED+silicone
Mount Options	◆
Finish Colour	White

Features

Marketing Feature 1	Single colour flexible SMD LED strip with 3M self adhesive backing
Marketing Feature 2	Cut points every 25mm
Marketing Feature 3	50m reel lengths
Marketing Feature 4	Maximum run of 10m with single end feed
Marketing Feature 5	Maximum run of 20m with double ended feed
Marketing Feature 6	CRI90
Marketing Feature 7	New quick connector accessories available
Marketing Feature 8	L80 B10 50,000hrs
Marketing Feature 9	5 Year Warranty

Apex Park | 6 Little Burrow | Welwyn Garden City AL7 4SW | United Kingdom | Tel: +44 (0) 1707 228 700

This document is uncontrolled if printed, all information is subject to change. Generated on 17/04/26