

SL130

1W LED spike light



1W at 350mA or 2W at 700mA



Coastal protected



IP65 ideal for outdoor areas

Features

| | |
|------------------------|-------------|
| IP rating | IP65 |
| CSP Switchable | Single CCT |
| Tiltable | 90° |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Rotation Angle | No |

Installation Information

| | |
|-----------------------------|--------------------|
| Input | 350mA / 700mA |
| Maximum Ambient Temperature | 35°C |
| Weight | 400g |
| Inrush Current | N/A |
| Construction Material | Anodised aluminium |
| UK Bathroom Zone | 1 |
| Electric Class (1, 2, 3) | 3 |
| Earth Leakage | N/A |
| Suitable for coastal areas | Yes |

Guarantee

Warranty 7 years

Features & benefits

- Long spike included for extra stability
- Robust cable for outdoor use
- Small & discreet

Photometrics @ 25°C

| Product Code | Finish | Colour | Beam | 350mA | | | | 700mA | | | | Energy |
|--------------|---------------------------|--------|------|-------|----|------|---------|-------|-----|------|---------|--------|
| | | | | W | lm | lm/W | lx @ 1m | W | lm | lm/W | lx @ 1m | |
| SL13040 | Black anodised aluminium | 4000K | 26° | 1W | 95 | 95 | 267 | 2W | 140 | 70 | 393 | A+ F |
| SL13030 | Black anodised aluminium | 3000K | 26° | 1W | 75 | 75 | 210 | 2W | 135 | 68 | 379 | A+ F |
| SL13027 | Black anodised aluminium | 2700K | 26° | 1W | 70 | 70 | 196 | 2W | 120 | 60 | 337 | A+ F |
| SL130ZMBX27 | Bronze anodised aluminium | 2700K | 26° | 1W | 70 | 70 | 196 | 2W | 120 | 60 | 337 | A+ F |
| SL130ZMBX30 | Bronze anodised aluminium | 3000K | 26° | 1W | 75 | 75 | 210 | 2W | 135 | 68 | 379 | A+ F |

Energy rating is a reflection of the LED light source.

Wiring Information

| | |
|-------------------------|---|
| Cable / Flying Lead | 3m H05RN-F rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |
| Input Cable Type | (H05RN-F) rubberised cable (outside diameter: 6mm) |


LED Driver

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|-------------|----------|------|---------|---------------|-----|-----|
| PLU/350 1-9 | 220-240V | Yes | No | 1 | 1 | 9 |
| PLU/700 3-9 | 220-240V | Yes | No | 1 | 3 | 9 |
| PSIP70018W | 220-240V | Yes | No | 1 | 1 | 8 |

Accessories

| | | |
|-----------------|--|-----------------|
| JB2 / JB4 / JB6 | Waterproof junction box / Gel filled waterproof connectors | Sold Separately |
| WCR 275 BLACK | 2-core rubber cable | Sold Separately |
| PDC/GRID DIMMER | 1-10V dimmer module | Sold Separately |

Beam angle: 26°



Ø42mm

