



2.2W at 350mA or 4.6W at 700mA



Coastal protected



IP65 ideal for outdoor areas

## SL230 Single Head

Low voltage single head LED spike light

### Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	90°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	330°

### Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	50°C
Weight	1.05
Inrush Current	N/A
Construction Material	Anodised aluminium
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

### Guarantee

Warranty 7 years

### Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution
- Choice of material finish to suit different styles
- Choose from a range of hoods for reduced glare.

### Photometrics @ 25°C

Product Code	Finish	Colour	Beam	W	lm	lm/W	lx @ 1m	W	lm	lm/W	lx @ 1m	Energy
				<b>350mA</b>				<b>700mA</b>				
SLX230SHB30	Black	3000K	40°	2.2W	300	136	682	4.6W	520	113	1182	A A E
SLX230SHA30	Anthracite	3000K	40°	2.2W	300	136	682	4.6W	520	113	1182	A A E

Energy rating is a reflection of the LED light source.

### Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) 2 CORE rubberised cable (OD: 6mm)

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	4
PLU/700 3-9	220-240V	Yes	No	1	1	4
PSIP70018W	220-240V	Yes	No	1	1	3

### Accessories

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately

Beam angle: 40°

