

DATASHEET



CU9NL

13A 2G DP Switched Socket with Photocell Nightlight Function

www.mlaccessories.co.uk

MLA PART CODE	CU9NL
DESCRIPTION	13A 2G DP Switched Socket with Photocell Nightlight Function
NET WEIGHT (KG)	0.185
FINISH	White
DIMENSIONS (MM)	Height - 88 Width - 148 Depth - 36 Projection - 12.45 Recessed Depth - 23.55
MINIMUM MOUNTING BOX DEPTH	25-35mm (dependent on wiring conditions)
CONSTRUCTION	Construction - Thermoset resin
CLASS	I
IP RATING	IP20
WATTAGE (W)	0.8
LAMP TECHNOLOGY	LED
LUMENS (LM)	55
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	73.1
CCT	4000K
CRI	>85
RUNNING CURRENT (A)	0.01
INPUT VOLTAGE	230V 50Hz
SWITCH TYPE	Double Pole
EARTH TERMINAL	Yes
LOAD/MAX. LOAD	13A
TERMINAL CAPACITY	3 x 2.5mm ² or 2 x 4.0mm ²
ADDITIONAL FEATURES	Built in Night Light
ANTI-MICROBIAL PROPERTIES	Inherent properties
SENSOR TYPE	Photocell
SENSOR OVERRIDE	No
SENSOR LUX SETTINGS	On 5-15 lux, off 20-40 lux, non-adjustable

WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598, BS EN 62493, BS 1363-2
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270870206

Date Created: 16/01/2026 15:06

