

SPECIFICATION



Chatsworth III Pro 2ft & 4ft

LED Non Corrosive Fitting



Beam Angle
120°



Input
200-240V



Life Hours
50,000



Dimmable
Available



Colour Temperature
3000K 4000K 6000K



	2ft Single	4ft Single	4ft Twin
Part Number	CH3P-2S	CH3P-4S	CH3P-4T
Selectable Wattage	11W/14W/17W/20W	11W/14W/17W/20W	21W/27W/32W/38W
Max Lumens	3000	3000	5700
Max Power	20W	20W	38W
Switch Time	25,000	25,000	25,000
Instant Light	Yes	Yes	Yes
Dimensions (mm)	650x85x79	1200x85x79	1200x105x79
Plug in Microwave	LINP-MW		
Plug in 3hr Emergency	LINP-EM		
Microwave	CH3P-2SMW	CH3P-4TMW	
3Hr Emergency	CH3P-2SEM	CH3P-4TEM	
3Hr Emergency & Microwave	CH3P-2SEM MW	CH3P-4TEM MW	

Key Features

- Selectable 3CCT & 4 Power
- Plug in Internal Microwave/Corridor Function and 3hr Emergency
- Polycarbonate construction
- Stainless steel clips
- Suitable for indoor and outdoor use
- Complete with fixing accessories
- 5 year warranty



Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.