




Falcon Multi Power Tri Colour Fire rating down light Installation Instructions



IMPORTANT INSTALLATION INFORMATION: This product must be installed in accordance with the latest edition of Building Regulations and carried out by a qualified electrician in accordance with the latest IEE Wiring Regulations. Before commencing any installation or maintenance work, ensure that the mains supply is switched off and the appropriate MCB or fuse is isolated.

Caution, risk of electric shock.

Falcon Multi Power, Tri Colour Fire rating down light

A choice of three bezels are available, Brushed Satin Chrome, Chrome and Black. Switch selectable colour's: 3000K (Warm White), 4000K (Daylight) and 6500K (Cool White). Switch selectable power: 5W, 8W Diamond recommend the Varilight® Pro JQP401W dimmer, operating a minimum of two and a maximum of 100 watts, i.e. 12. The Falcon feature push fit connectors for ease of installation with loop in, loop out terminals.



Mains input voltage: 220-240VAC 50/60 Hz

Power consumption: 5 or 8 watts

Rated at IP65

Hole cut out 70mm

CRI: Ra>80

CCT: 3000K, 4000K & 6500K

Lumen 5W: 530lm, 570lm, 550lm

Lumen 8W: 745lm, 860lm, 770lm

Fire rated mains fixed downlight suitable for 30/60/90 minute plasterboard ceilings.

