



MZ520N

Auxiliary contact for motor starter 1C+10
230/400V AC

Architecture

Fixing mode

Side mounting

Main electrical features

Rated operational voltage Ue

220 V
500 V

Frequency

40/60 Hz

Rated current

1 A

Type of supply voltage

AC

Voltage

Rated insulation voltage	690 V
--------------------------	-------

Rated impulse withstand voltage	6000 V
---------------------------------	--------

Electric current

Acceptable current rating with AC1	3 A
------------------------------------	-----

Dimensions

Depth of installed product	68 mm
----------------------------	-------

Width of installed product	9 mm
----------------------------	------

Power

Total power loss under IN	0.04 W
---------------------------	--------

Endurance

Electric endurance in number of cycles	50000
--	-------

Number of mechanical operations	100000
---------------------------------	--------

Capacity

Number of modules	0.5
-------------------	-----

Installation, mounting

Tightening torque	1,3Nm
-------------------	-------

Connection

Connection cross-sect. flexible conductor	2,5mm²
---	--------

Connection cross-sect. rigid cable	2,5mm²
Type of connection	with screw
Type of contacts	1NC+1NO

Accessories included

Type of accessory	Hilfsschalter / Fehlersignalschalter
-------------------	--------------------------------------

Equipment

Number of auxiliary contacts as normally closed contact	1
Number of auxiliary contacts as normally open contact	1
Can be accessorized	No

Standards

European directive WEEE	concerned
-------------------------	-----------

Safety

Protection index IP	IP20
---------------------	------