


Loox5 distributors



Häfele Loox5 box to box 2-way distributor with switching function for 1 switch



1 switch controls all output ports



- > Area of application: Box to box plug-in connection
The connection of the distributors with the driver can be done via a box to box plug-in connection or via an extension lead. Any number of distributors can be connected to the driver
- > Version: With switching function for 2 outputs
- > Material: Plastic
- > Colour: Black
- > Dim. (L x W x H): 60 x 50 x 16 mm
- > Number of connections: Input ports: 1 plug, Loox5 2-pin 12V box-to-box
Outputs: 1 socket, Loox5 2-pin 12V box to box
Switched outputs: 2 sockets, Loox5 2-pin 12V
Control inputs: 1 socket, Loox switch
- > Supplied with: 1 distributor including fixing materials

Voltage	Max. connected wattage W	Cat. No.
5 12V	60	833.95.901
5 24V	120	833.77.843




Ensure maximum connected wattage is not exceeded



Häfele Loox5 2-way distributor with switching function for 1 switch



1 switch controls all output ports



- > Area of application: Any number of distributors can be connected to the driver
- > Version: With switching function for 2 outputs
- > Material: Plastic
- > Colour: Black
- > Dim. (L x W x H): 60 x 50 x 16 mm
- > Number of connections: Input ports: 1 plug, Loox5 2-pin 24V
Outputs: 2 sockets, Loox5 2-pin 24V
- > Supplied with: 1 distributor with lead

Voltage	Max. connected wattage W	Cat. No.
5 12V	60	833.95.902
5 24V	120	833.77.842



Ensure maximum connected wattage is not exceeded

Loox5 converters

1

UK
CA IP20


Häfele Loox5 converter for 24 V devices on a 12 V driver



- > With switching function for 6 output ports
- > Box to box plug connection
- > The connection of the distributors with the driver can be done via a box to box plug-in connection or via an extension lead

- > Version: For 24 V devices on a 12 V driver
- > Input ports: 1x plug, Loox5 2-pin 12 V box to box
- > Outputs: 1x socket, Loox5 2-pin 24 V box to box
- > Connected output ports: 6x sockets, Loox5 2-pin 24 V
- > Connected input ports: 1x socket, Loox switch
- > Material: Plastic
- > Colour: Black
- > Dim. (L x W x H): 120 x 50 x 16 mm
- > Supplied with: 1 converter including fixing materials (adhesive tape and screws)

Voltage	Power consumption W	Output power W	Cat. No.
5 12V 5 24V	60	50	833.77.846

- ! Make sure the connected load at the driver is sufficient.
Max. 50 W connected load per converter possible

Häfele Loox5 converter for 12 V devices on a 24 V driver



- > With switching function for 6 output ports
- > Box to box plug connection
- > The connection of the distributors with the driver can be done via a box to box plug-in connection or via an extension lead

- > Version: For 12 V devices on a 24 V driver
- > Input ports: 1x plug, Loox5 2-pin 24 V box to box
- > Outputs: 1x socket, Loox5 2-pin 12 V box to box
- > Connected output ports: 6x sockets, Loox5 2-pin 12 V
- > Connected input ports: 1x socket, Loox switch
- > Material: Plastic
- > Colour: Black
- > Dim. (L x W x H): 120 x 50 x 16 mm
- > Supplied with: 1 converter including fixing materials (adhesive tape and screws)

Voltage	Power consumption W	Output power W	Cat. No.
5 24V 5 12V	60	50	833.77.847

- ! Make sure the connected load at the driver is sufficient.
Max. 50 W connected load per converter possible