

Luminaires | Fire Rated Downlights

EFD™ PRO Fixed / IP Rated Fire Rated Downlight

AU-DLM981CSWCP



Photometrics

Colour Temperature	CCT
UGR19	No
Type of Distribution	Symmetric

Product Features

Brand	Aurora
IP Rating	IP20
SKU Type	Fixed/IP65
Dimmable	Yes
Fire Protection	Yes
Warranty	7 Years
Country of Origin	CN

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	Ac
Surge Protection (kV)	1500
Protection Class	Class 1

Fire Protection	Yes
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Min) °C	25
Operating Temp. (Max) °C	45
Glow Wire Test (°C)	650

Physical Attributes

Height (mm)	107
Overall Diameter (mm)	90
Lamp Base	No
Cutout Diameter Min. (mm)	75
Cutout Diameter Max. (mm)	75
Material	Polycarbonate & Pressed Steel
Mount Options	Recessed

Features

Marketing Feature 1	Interchangeable twist & lock bezels available
Marketing Feature 2	LENNEL terminals
Marketing Feature 3	Fibre based insulation coverable up to 300mm (LED only)
Marketing Feature 4	Tested in 30, 60 & 90 min fire rated ceilings
Marketing Feature 5	Fire tested with solid timber, ijoist and metal web joists
Marketing Feature 6	White bezel included
Marketing Feature 7	7 year warranty