

DATASHEET



HEX2

HELIX ONE 2FT 230V IP66 IK10 22W Modular Non-Corrosive Fitting - 4000K

www.mlaccessories.co.uk

MLA PART CODE	HEX2
DESCRIPTION	HELIX ONE 2FT 230V IP66 IK10 22W Modular Non-Corrosive Fitting - 4000K
NET WEIGHT (KG)	1.1
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 665 Height - 81 Width - 126 Projection - 81
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP66
IK RATING	IK10
WATTAGE (W)	22
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3045
LUMENS LIGHT SOURCE ONLY (LM)	3695
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	162
CIRCUIT WATTAGE (W)	22.7
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.107
SVM	0.076
PST-LM	0.03
BEAM ANGLE (DEGREES)	110
L70B50 LIFESPAN (HRS)	70,000
LED COMPATIBLE	Yes
DIMMABLE	No
EMERGENCY CONVERSION KIT	MODEMKIT2
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270892024

Date Created: 23/06/2026 12:54