

## DATASHEET



### HEX5EM

**HELIX ONE 5FT 230V IP66 IK10 26W Modular Non-Corrosive Fitting with Dual Mode Emergency - 4000K**

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)

MLA PART CODE	HEX5EM
DESCRIPTION	HELIX ONE 5FT 230V IP66 IK10 26W Modular Non-Corrosive Fitting with Dual Mode Emergency - 4000K
NET WEIGHT (KG)	2.05
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1565 Height - 81 Width - 95 Projection - 81
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP66
IK RATING	IK10
WATTAGE (W)	26
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3805
LUMENS LIGHT SOURCE ONLY (LM)	4425
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	167
LUMENS EMERGENCY MODE (LM)	390
CIRCUIT WATTAGE (W)	26.42
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.127
SVM	0.067
PST-LM	0.006
BEAM ANGLE (DEGREES)	115
L70B50 LIFESPAN (HRS)	70,000
LED COMPATIBLE	Yes
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	Switchable Manual / Self-test
OPERATING TEMPERATURE	0 ~ 45°C
MINIMUM CHARGING TEMPERATURE	0°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
BATTERY TYPE	LiFePO4
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270895445

Date Created: 23/06/2026 11:22