

DATASHEET



HEXMCF4

HELIX MAX 4FT 230V IP66 IK10 Quad Wattage Tri-CCT Modular Non-Corrosive Fitting with Corridor Sensor

www.mlaccessories.co.uk

MLA PART CODE	HEXMCF4
DESCRIPTION	HELIX MAX 4FT 230V IP66 IK10 Quad Wattage Tri-CCT Modular Non-Corrosive Fitting with Corridor Sensor
NET WEIGHT (KG)	1.55
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1265 Height - 81 Width - 95 Projection - 81
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP66
IK RATING	IK10
WATTAGE (W)	22/27/33/39
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3110/3350/3190/3810/4045/3830/4555/4975/4695/5235/5800/5520
LUMENS LIGHT SOURCE ONLY (LM)	6640
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	171
CIRCUIT WATTAGE (W)	38.7
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.175
SVM	0.009
PST-LM	0.043
BEAM ANGLE (DEGREES)	120
L70B50 LIFESPAN (HRS)	70,000
LED COMPATIBLE	Yes
DIMMABLE	Corridor dimming function only
EMERGENCY CONVERSION KIT	MODEMKIT2
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
WARRANTY	7year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270893434

Date Created: 23/06/2026 12:34