

DATASHEET



HEXMCF5

HELIX MAX 5FT 230V IP66 IK10 Quad Wattage Tri-CCT Modular Non-Corrosive Fitting with Corridor Sensor

www.mlaccessories.co.uk

MLA PART CODE	HEXMCF5
DESCRIPTION	HELIX MAX 5FT 230V IP66 IK10 Quad Wattage Tri-CCT Modular Non-Corrosive Fitting with Corridor Sensor
NET WEIGHT (KG)	1.85
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1565 Height - 81 Width - 95 Projection - 81
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP66
IK RATING	IK10
WATTAGE (W)	28/34/41/49
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3970/4340/4065/4820/5265/4915/5680/6270/5900/6670/7380/6900
LUMENS LIGHT SOURCE ONLY (LM)	8335
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	167
CIRCUIT WATTAGE (W)	49.78
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.221
SVM	0.007
PST-LM	0.021
BEAM ANGLE (DEGREES)	120
L70B50 LIFESPAN (HRS)	70,000
LED COMPATIBLE	Yes
DIMMABLE	Corridor dimming function only
EMERGENCY CONVERSION KIT	MODEMKIT2
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
WARRANTY	7year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270893458

Date Created: 23/06/2026 12:38