

DATASHEET



HEXMCF6

HELIX MAX 6FT 230V IP66 IK10 Quad Wattage Tri-CCT Modular Non-Corrosive Fitting with Corridor Sensor

www.mlaccessories.co.uk

MLA PART CODE	HEXMCF6
DESCRIPTION	HELIX MAX 6FT 230V IP66 IK10 Quad Wattage Tri-CCT Modular Non-Corrosive Fitting with Corridor Sensor
NET WEIGHT (KG)	2.35
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1865 Height - 81 Width - 95 Projection - 81
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP66
IK RATING	IK10
WATTAGE (W)	34/42/51/60
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	4870/5310/5020/4885/6490/6100/7060/7720/7215/8120/8830/8425
LUMENS LIGHT SOURCE ONLY (LM)	10280
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	168
CIRCUIT WATTAGE (W)	61.02
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.269
SVM	0.004
PST-LM	0.035
BEAM ANGLE (DEGREES)	120
L70B50 LIFESPAN (HRS)	70,000
LED COMPATIBLE	Yes
DIMMABLE	Corridor dimming function only
EMERGENCY CONVERSION KIT	MODEMKIT2
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
WARRANTY	7year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270893472

Date Created: 23/06/2026 12:41