

DATASHEET



HEXSCW2

**HELIX SHIFT 2FT 230V IP66 IK10 Quad Wattage
Modular Non-Corrosive Fitting - CCT Adjustable**

www.mlaccessories.co.uk

| MLA PART CODE | HEXSCW2 |
|--|--|
| DESCRIPTION | HELIX SHIFT 2FT 230V IP66 IK10 Quad Wattage Modular Non-Corrosive Fitting - CCT Adjustable |
| NET WEIGHT (KG) | 1.1 |
| FINISH | Grey |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Length - 665 Height - 81 Width - 125 Projection - 81 |
| CONSTRUCTION | Construction - Polycarbonate |
| CLASS | I |
| IP RATING | IP66 |
| IK RATING | IK10 |
| WATTAGE (W) | 13/15/18/22 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 1715/1855/1775/2020/2200/2070/2380/2605/2465/2790/3010/2850 |
| LUMENS LIGHT SOURCE ONLY (LM) | 3610 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 168 |
| CIRCUIT WATTAGE (W) | 21.4 |
| CCT | 3000/4000/5700K |
| LIGHT COLOUR | CCT |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.103 |
| SVM | 0.021 |
| PST-LM | 0.26 |
| BEAM ANGLE (DEGREES) | 110 |
| L70B50 LIFESPAN (HRS) | 70,000 |
| LED COMPATIBLE | Yes |
| DIMMABLE | No |
| EMERGENCY CONVERSION KIT | MODEMKIT2 |
| OPERATING TEMPERATURE | -20~45°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE ENTRY (MM) | 20 |
| CABLE GLAND INCLUDED | Compression gland |
| WARRANTY | 7year(s) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270892529 |

Date Created: 23/06/2026 12:44