PRODUCT DATA SHEET

Aurora AU-WP103CWSPH

UtiliteXL™ 14W-24W IP65 Colour & Wattage Switchable Wall Pack Photocall

Manufacturer: Aurora Lighting UK

GTIN: 5056102064780

Family: Luminaires

Range: Wall





DESCRIPTION

Designed to last in a tough environment, the UtiliteXL™ wall pack with cast aluminium base and polycarbonate diffuser is available in standard, photocell and emergency versions with black housing.

- Colour switchable between 3000K/4000K/6500K
- Polycarbonate body and diffuser
- Side and rear entry
- IP65 rated
- IK10 rated
- IK10 rated
- 5 Year Warranty
- 3 year on-site warranty (registration required) *Terms and conditions apply
- Wattage switchable between 14, 17, 21, 24W
- Emergency pack available to purchase separately (AU-EM4)

TECHNICAL SPECIFICATION

ETIM Class: Ceiling / wall luminaire (EC002892)

Primary Features

Colour of light	White	Light source included	Yes
Colour temperature (K)	3000 - 6500	Light source type	Other
Housing colour	Other	Maximum system power (W)	24
Lamp cap/base	Other	Nominal voltage (V)	240 - 240
Lamp power (W)	14 - 24	Voltage type	AC

Additional Features

Beam angle	Extreme wide beam >80°	Protection class according to IEC 61140	I
Colour consistency (McAdam ellipse)	SDCM6	Rated life time L70/B50 at 25 °C (h)	50000
Colour rendering index (CRI/Ra)	80-89	Recess height/depth (mm)	217
Colour temperature switchable	No	Recess length (mm)	309
Control gear	Not required	Recess width (mm)	162
Dimming DALI	No	Suitable for ceiling mounting	Yes
Fit for workplace acc. EN 12464-1	No	Suitable for emergency lighting	No
Height/depth (mm)	217	Suitable for light line configuration	No
Housing material	Other	Suitable for recessed mounting	No
Impact resistance (IK rating)	IK10	Suitable for surface mounting	Yes
Length (mm)	309	Suitable for suspended mounting	No
Light distribution	Symmetric	Type of grid	None
Light outlet	Direct	Width (mm)	162
Luminaire may be covered with thermally insulating material	No	With air slots	No
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No	With light sensor	No
Power factor	0.9	With movement sensor	Yes

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 22-11-2024

Trade Tariff Commodity Code: Not supplied

Country of Origin: CN

Aurora Lighting UK, Apex Park, 6 Little Burrows, Burrowfields, Welwyn Garden City, AL7 4SW
01727 83 66 11 info@auroralighting.com https://auroralighting.com/

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 17/11/2026.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.